



Servial CC A/S
Ramløsevej 59
3200 Helsingør

SHEET OF APPROVAL

For F&P-registration of Mechanical Security Units

No. of approval	Colour	Description	Date of approval
10.211-00008	RED	SECURE	12.10.2004
Mechanical security unit - tested		Main group 1	
Type designation of unit: Container lock, CC Bearing Bracket			
<p>The unit may be launched as F&P approved. When installed the unit must be provided with a visible identity label, cf. "General conditions". The classification colours are YELLOW, GREEN, BLUE or RED, RED representing the highest class of security. The approval may be revoked if the unit is altered or in case of new know-how.</p>			
<p>The approval is valid until: 12.10.2014 and may be extended if the owner of the approval has applied for this 6 months before date of expiry at the latest.</p>			
Remarks: Interlocking with lock in security class (minimum) BLUE. Mounting of lock: Self-locking nuts from the inside.			
General conditions - see page 2.			
Danish Insurance Association: 08.04.2009			
 Forsikring & Pension Amaliegade 10 1256 København K. Tlf.: 33 43 55 00		 Maiken Skriver Poulsen	

General Conditions for the Installation of F&P-Approved Security Units

- Security units must be installed according to the instructions of the manufacturer/owner of the approval.
- Security units approved according to the “Standard Thief Method”, main group 1, must be fixed onto a stable building component of a quality that, as a minimum, corresponds to the classification of the security unit.
- Security units approved according to the “Standard Thief Method”, main group 2: Units weighing less than 250 kg must be fixed onto a stable building component of a quality that, as a minimum, corresponds to the strength of the security unit.
- Electrically operating security units (gratings, roll-fronts, etc.) must be operated by key and/or controlled by electronic monitoring system. The cylinder locks used must be Skafor approved.
- In a grating/plate cupboard, the key operating unit must be installed as an internal, integrated part of the security unit so that the cylinder lock is operated through the interface of the security unit.
- In mechanical security cells the key operating unit, if any, must be installed in a way so that only the cylinder lock is available in the interface of the security cell.
- If an electronic monitoring system has been established, the key operating unit must be installed in an area monitored by a movement detector.

Classified security units, cf. the “Standard Thief Method”, must be provided with a visible label stating the unit’s no. of approval, classification, and the name ”Danish Insurance Association”. If however a visible marking is not possible for instance for reasons of lack of space, an exemption from marking can be granted on application to F&P.

Yours sincerely,
Danish Insurance Association